

Preference Change: A Quantitative Approach*

Fenrong Liu

Department of Philosophy, School of Humanities and Social Sciences, Tsinghua University

fenrong@tsinghua.edu.cn

Abstract. In this paper we present a quantitative semantic of preference in terms of evaluation functions. A new language with propositional constants is proposed and it turns out to be both concise and expressive. Moreover, such a quantitative perspective suggests a different way to deal with preference changes when processing new information. We follow the standard mechanism of product update, and propose a new Addition rule and a new Parameterized rule to characterize the subtleties of value changes. A complete dynamic epistemic evaluation logic is presented for the evaluation update. We then shift to the deontic setting and show that the current mechanism applies there as well, in particular, it provides a way to solve the issue of contradictory obligations. Finally, we end up with a new technical result concerning bisimulation for evaluation models.

1. Introduction

Preference is what colors our view of the world, and it drives the actions that we take in it. Moreover, suggestions, commands and other triggers continually change our preferences on the basis of new information that they bring. The dynamics of preference has been studied extensively in the recent years, see literature, e.g., [15], [10], [19], [17], [13] and [14]. While a *qualitative* approach was undertaken in those previous work, this paper will take a more *quantitative* approach by introducing an evaluation function. This way, it becomes possible to consider the subtlety of information processing and to see how new information affects our evaluation that results in a preference change.

First we would like to say a few words on “logical dynamics” in general. There is a growing tradition in logic modeling changes in epistemic or doxastic states. Agents receive new information and update their knowledge or beliefs accordingly. This style of thinking can be traced back to the early 1980s, e.g., the well-known *AGM* postulates handling belief change ([1]). In what follows, we will work with a

Received 2009-7-12

*This research is supported by the projects with grant numbers: 08JC72040002 and 09CZX033. The paper was first presented at the LOFT 2006 in Liverpool, I thank its anonymous reviewers and its audience for their comments and questions. The paper has undergone a few rounds of revision, I thank Johan van Benthem, Ulle Endriss, Dick de Jongh, Eric Pacuit, Floris Roelofsen, Brian Semmes, Tomoyuki Yamada, Jonathan Zvesper for their helpful comments. Finally, I thank Yuan Ren, Minghui Xiong and Qihong Pan for their suggestions and help in the process of publishing the paper in the current journal.

recent approach called *dynamic epistemic logic DEL*(cf. [5, 7, 12, 23], and [11], as well as recent work on belief revision in [6, 8]). Preference change can be dealt with by using the same methodology of modeling information dynamics, as systematically shown in [19]. The present paper continues this line.

When seeing things quantitatively, the kind of situation to be thought of is: Suppose that Alice plans to buy a new apartment. There are two candidate apartments d_1 and d_2 available, located in different places. She has her own judgement based on her current knowledge: they could be equally preferable, or one is more preferable than the other. To mark her evaluation difference, she assigns two numbers to d_1 and d_2 , respectively. A newspaper article that “the government is planning to build a park near d_1 ” may *increase* her value for d_1 . In contrast, getting to know that the criminal rate is going up in the neighborhood of d_1 may *decrease* her value for d_1 . The idea is: one starts off with the initial values of the options, and keep *scoring* in accordance with the new information, either adding points if the information has a positive influence on the option, or dropping points in case it has a negative effect, the number zero is added when it does not have any effect or is irrelevant. Altogether this brings about an evaluation change from which the preference change can be induced.

2. An evaluation language and model

Following [25] and [3], a language of graded preference modalities is introduced to indicate the strength of preference. Here we take a simple design ([18]), which is more workable and perspicuous.

Definition 1 (Language) *Let a finite set of proposition variables Φ and a finite set of agents G be given. The epistemic evaluation language \mathcal{L} is defined by the rule*

$$\varphi := \top \mid p \mid \neg\varphi \mid \varphi \wedge \psi \mid q_a^m \mid K_a\varphi$$

where $p \in \Phi$, $a \in G$, and $m \in \mathbb{Z}$.

A propositional constant q_a^m is added to the language for each agent $a \in G$ and each value $m \in \mathbb{Z}$. The intended interpretation of the formula q_a^m is ‘the agent a assigns the state where she stands the value at most m ’, and the intended interpretation of the formula $K_a\varphi$ is ‘the agent a knows that φ ’. We will see that the language of [3], \mathcal{L}_A , can be simplified with this language.

Definition 2 (Evaluation models) *An evaluation model for the epistemic evaluation language is a tuple $\mathcal{M} = (S, \{\sim_a \mid a \in G\}, \{v_a \mid a \in G\}, V)$ ¹ such that S is a non-empty set of states, \sim_a is an epistemic equivalence relation on S , v_a is an evaluation function*

¹ I will sloppily write it as $\mathcal{M} = (S, \sim_a, v_a, V)$ when G is clear from the context.

assigning each state an element from $\{-\infty\} \cup \mathbb{Z} \cup \{\infty\}^2$, and V is a function assigning to each proposition variable p in Φ a subset $V(p)$ of S .

Evaluation functions induce a total ordering in an obvious way, namely, from $v_a(s) \leq v_a(t)$ we can obtain $s \preceq_a t$. In this manner, we are making use of the information about the qualitative ordering encoded in the evaluation functions. However, we will see that the quantitative information part will play a big role in many situations in the following sections. For instance, considering information about the intensity of preference will lead to a new definition of bisimulation.

Definition 3 (Truth conditions) *Suppose s is a state in a model $\mathcal{M} = (S, \sim_a, v_a, V)$. Then we inductively define the notion of a formula φ being true in \mathcal{M} at state s in what follows:*

- $\mathcal{M}, s \models \top$
- $\mathcal{M}, s \models p$ iff $s \in V(p)$, where $p \in \Phi$
- $\mathcal{M}, s \models \neg\varphi$ iff not $\mathcal{M}, s \models \varphi$
- $\mathcal{M}, s \models \varphi \wedge \psi$ iff $\mathcal{M}, s \models \varphi$ and $\mathcal{M}, s \models \psi$
- $\mathcal{M}, s \models K_a\varphi$ iff for all $t \in S$ such that $s \sim_a t$ and $\mathcal{M}, t \models \varphi$
- $\mathcal{M}, s \models q_a^m$ iff $v_a(s) \leq m$, where $m \in \mathbb{Z}$.

For the sake of comparison, we give the definition for $B_a^m\varphi$ in [3] as follows,

- $\mathcal{M}, s \models B_a^m\varphi$ iff for all $t \in S$ such that $s \sim_a t$ and $v_a(t) \leq m$, $\mathcal{M}, t \models \varphi$.

Theorem 1 (Soundness) *Epistemic Evaluation Logic (EEL) consists of the following axioms and derivation rules. Furthermore, it is sound w.r.t. evaluation models.*

1. All propositional tautologies
2. $K_a(\varphi \rightarrow \psi) \rightarrow (K_a\varphi \rightarrow K_a\psi)$
3. $K_a\varphi \rightarrow \varphi$
4. $K_a\varphi \rightarrow K_aK_a\varphi$
5. $\neg K_a\varphi \rightarrow K_a\neg K_a\varphi$
6. $q_a^m \rightarrow q_a^n$ for all $m \leq n \in \mathbb{Z}$
7. From $\vdash \varphi$ and $\vdash \varphi \rightarrow \psi$ infer $\vdash \psi$
8. From $\vdash \varphi$ infer $\vdash K_a\varphi$.

We take the standard notion of proof. In case a formula φ is provable in *EEL*, we write $\vdash_{EEL} \varphi$.

Theorem 2 (Completeness) *The logic EEL is complete w.r.t. evaluation models.*

²In [3] the range is natural numbers up to a maximal element (*Max*). The values are normalized to *Max*. For me the distance between the numbers seems essential, so normalization is not an option. Similarly I like to be able to subtract unrestrictedly.

Proof The proof is standard. First we define the canonical model w.r.t.: $\mathcal{M}^c = (S^c, \sim_a, v_a, V)$

- $S^c = \{s_S: S \text{ maximal } EEL\text{-consistent set}\}$
- $\sim_a = \{(s_S, s_T): S/K_a \subseteq T\}$ where $S/K_a = \{\varphi: K_a\varphi \in S\}$
- $v_a(s_S) = \min\{m: q_a^m \in S\}$ (∞ if $\{m: q_a^m \in S\}$ is empty, $-\infty$ if $\{m: q_a^m \in S\} = \mathbb{Z}$.)
- $s_S \in V(p)$ iff $p \in S$.

We need to show that

$$\varphi \in T \text{ iff } \mathcal{M}^c, s_T \models \varphi.$$

By induction on the structure of the formula φ . We only consider the case of the constant q_a^m :

(\Rightarrow) Assume $q_a^m \in T$. We have $v_a(s_T) \leq m$. Then by Definition 3, we get $\mathcal{M}^c, s_T \models q_a^m$.

(\Leftarrow) Assume $\mathcal{M}^c, s_T \models q_a^m$. We know $q_a^{v_a(s_T)} \in T$ and $v_a(s_T) \leq m$. By axiom 6, $q_a^{v_a(s_T)} \rightarrow q_a^m$. So, we get $q_a^m \in T$. This is to say that we have proved that

Every *EEL*-consistent set Γ of formulas is satisfiable in some epistemic model.

The completeness result follows. □

To conclude this section we look at the relation between \mathcal{L}_A and \mathcal{L} . From \mathcal{L}_A to \mathcal{L} , we can define a translation: a formula of the form $B_a^m\varphi$ is translated into $K_a(q_a^m \rightarrow \varphi)$. This is to say that in the language \mathcal{L} , we can express the same notions as [3] without introducing additional epistemic operators. This advantage leads to the much simpler completeness proof we have just seen. It becomes even more prominent when constructing reduction axioms for dynamics in the later sections. On the other hand, we can easily translate \mathcal{L} back into \mathcal{L}_A : q_a^m will be $\neg B_a^m \perp$, which means that \mathcal{L}_A and \mathcal{L} are equivalent.

Having set up the base language for evaluation models, we now proceed to the dynamic superstructure that we have in mind.

3. Finer modelling of evaluation changes

3.1 Preliminaries: product update

As we have mentioned in the introduction, to model knowledge change due to incoming information, the most powerful mechanism is dynamic epistemic logic. In the following, we briefly recall its basic ideas and techniques.

Definition 4 (Event models) *An event model is a tuple $\mathcal{E} = (E, \sim_a, PRE)$ such that E is a non-empty set of events, \sim_a is a binary epistemic relation on E , PRE is a function from E to the collection of all epistemic propositions.*

The intuition behind the function PRE is that it gives the *preconditions* for an action: an event e can be performed at world s only if the world s fulfills the precondition $PRE(e)$.

Definition 5 (Product update) *Let an epistemic model $\mathcal{M} = (S, \sim_a, V)$ and an event model $\mathcal{E} = (E, \sim_a, PRE)$ be given, the product update model is defined to be the model $\mathcal{M} \otimes \mathcal{E} = (S \otimes E, \sim'_a, V')$ such as*

- $S \otimes E = \{(s, e) \in S \times E : (\mathcal{M}, s) \models PRE(e)\}$
- $(s, e) \sim'_a (t, f)$ iff both $s \sim_a t$ and $e \sim_a f$
- $V'(p) = \{(s, e) \in \mathcal{M} \otimes \mathcal{E} : s \in V(p)\}$.

The above notions suggests an extension of the epistemic language.

Definition 6 (Dynamic epistemic language) *Let a finite set of proposition variables Φ , a finite set of agents G , a finite set of events E be given. The dynamic epistemic language is defined by the rule*

$$\varphi := \top \mid p \mid \neg\varphi \mid \varphi \wedge \psi \mid K_a\varphi \mid [e]\varphi$$

where $p \in \Phi$, $a \in G$, and $e \in E$.

We could also add the usual action operations of composition, choice, and iteration from propositional dynamic logic to the event vocabulary - but in this paper, we will have no special use for these. The language has new dynamic modalities $[e]$ referring to epistemic events, and these are interpreted in the product update model as follows:

$$\mathcal{M}, s \models [e]\varphi \text{ iff } \mathcal{M} \otimes \mathcal{E}, (s, e) \models \varphi.$$

Reduction axioms in dynamic epistemic logic play an important role to encode the changes when the events take place. For example, the following axiom concerns agents' knowledge change.

$$[e]K_a\varphi \leftrightarrow PRE(e) \rightarrow \bigwedge_{f \in E} \{K_a[f]\varphi : e \sim_a f\}.$$

Intuitively, after an event e takes place the agent a knows φ , is equivalent to saying that if the event e can take place, a knows beforehand that after e (or any other event f which a can not distinguish from e) happens φ would hold.

The above update setting can be extended to preference change over evaluation models. We will make this precise below.

3.2 Evaluation product update

We have defined evaluation models in section 2. Now we need to do the same thing to event models.

Definition 7 (Evaluation event model) *A evaluation event model is a tuple $\mathcal{E} = (E, \sim_a, v_a, PRE)$ such that E is a non-empty set of events, \sim_a is a binary epistemic relation on E , v_a is an evaluation function assigning each action an element from \mathbb{Z} , PRE is a function from E to the collection of all epistemic propositions.*

Based on the values they assign to events, the evaluation functions v_a indicate which events agents prefer. Note that this is a major change as compared with standard uses of evaluation: we do not just evaluate static states of affairs, but also actions or events!

Definition 8 (Evaluation product update) *Let an evaluation model $\mathcal{M} = (S, \sim_a, v_a, V)$ and an evaluation event model $\mathcal{E} = (E, \sim_a, v_a, PRE)$ be given, the evaluation product update model is defined to be the model $\mathcal{M} \otimes \mathcal{E} = (S \otimes E, \sim'_a, v'_a, V')$ such that*

- $S \otimes E = \{(s, e) \in S \times E\}$
- $(s, e) \sim'_a (t, f)$ iff both $s \sim_a t$ and $e \sim_a f$
- $v'_a(s, e) = v_a(s) + v_a(e)$ (Addition rule)
- $V'(p) = \{(s, e) \in \mathcal{M} \otimes \mathcal{E} : s \in V(p)\}$.


Note that we keep all world/event pairs (s, e) represented, as these are the non-realized options that we can still have regrets about. For the evaluation update, we simply take the *sum* of the value for the previous state and that for the event. The Addition rule is best understood by looking at the example in the introduction again, though the evaluation event model there is quite simple and it contains only one event each time.

Example 1 Assume that in the initial model S_0 , agent a has the same evaluations towards s and t where d_1 would be chosen at s and d_2 at t . She gives 0 to both of them, pictured below:


s	t
0	0
0	0

S_0

Afterward, the newspaper brings in a new information “the government is planning to build a park near d_1 ” (denoted by p), it positively effects the value of s in the model S_0 , but has no effect on t . The initial model S_0 is updated to S_1 :



In the model S_1 , clearly, a would prefer d_1 over d_2 since the value for s' is greater than that for t' . The story goes on, the new information “the criminal rate is going up in the neighborhood of d_1 ”(denoted by q) causes values to decrease. The model changes in the following way:



With the evaluation changes, preference changes accordingly, agent a has no preference over d_1 and d_2 .

This example shows us how incoming information changes our values of the states. Although the event can be very complex, such a process goes on continuously, and eventually we prefer things with a higher score.

However, several issues remain to be discussed: First of all, the *sources* of information. As discussed extensively in various contexts, not all incoming information is equally reliable. In order to propose a realistic evaluation update rule, the *reliability* of information must be taken into account. Also, another key issue concerns the relative different *forces* of information. In multi-agent system, the same information may have different force for different agents. For instance, the agent a may take a piece of information seriously, while the agent b does not do so. These two aspects are parameterized in the following new update rule.

Definition 9 (Parameterized rule) *Let $\mu(e)$ be a reliability function, and $\lambda(e)$ a relative force function. The domains of these two functions are the set of events, and the ranges of these functions are \mathbb{N} .³ Given the value for the previous state s and event e , the new value for state (s, e) is defined by the following:*

$$v_a(s, e) = v_a(s) + v_a(e) \cdot \mu(e) \cdot \lambda(e).$$

Back to the first step of Example 1, suppose agent a only half trusts what the newspaper said, namely $\mu(e) = 5$. And the relative force of the park building information is 4, i.e. $\lambda(e) = 4$, which shows she thinks it is rather important. Then the

³In practice, one can choose a natural number between 0 and 10 to denote the reliability or the relative force.

value of s' in the model S_1 would be calculated as

$$v_a(s, e) = 0 + 1 \cdot 5 \cdot 4 = 20$$

With the Parameterized rule, we can better understand how information is being processed. But things need not stop here, one could propose other types of evaluation update rules to interpret more complex situations. For example, the agent may give more weight to the previous state (behave conservatively), which seems to call for a parameter associated with the value for s in the above rule, as was proposed for belief revision of diverse agents in [18] and [20]. Or in some situations, one needs to consider the dependence between information that comes later and that comes earlier. We will leave these issues for further investigation.

3.3 Dynamic epistemic evaluation logic

We are now ready to define a logic for dynamical evaluation update mechanisms. But in this section we confine ourselves to the Addition rule only.

Definition 10 (Dynamic epistemic evaluation language) *Let a finite set of proposition variables Φ , a finite set of agents G , and a finite set of events E be given. The dynamic epistemic language is defined by the rule*

$$\varphi := \top \mid p \mid \neg\varphi \mid \varphi \wedge \psi \mid q_a^m \mid K_a\varphi \mid [e]\varphi$$

where $p \in \Phi$, $a \in G$, $e \in E$, and $m \in \mathbb{Z}$.

Again, we will not include the usual action operations like composition, choice, etc. But we have formulas of the form $[e]q_a^m$, for which we will find reduction axioms.

Theorem 3 (Soundness) *Dynamic epistemic evaluation logic (DEEL) consists of the following formulas, and it is sound w.r.t. evaluation product update models:*

1. $[e]p \leftrightarrow p$
2. $[e]\neg\varphi \leftrightarrow \neg[e]\varphi$
3. $[e](\varphi \wedge \psi) \leftrightarrow [e]\varphi \wedge [e]\psi$
4. $[e]K_a\varphi \leftrightarrow PRE(e) \rightarrow \bigwedge_{f \in E} \{K_a[f]\varphi : e \sim_a f\}$
5. $[e]q_a^m \leftrightarrow q_a^{m-v_a(e)}$.

Proof To prove the validity of the above axioms, we consider two models: (\mathcal{M}, s) and $(\mathcal{M} \otimes \mathcal{E}, s)$ before and after the update. Axiom 1 says that the update will not change the objective valuation of atomic propositions. And axioms 2 and 3 are just Boolean operations, easy to see.

For axiom 4, the formula $[e]K_a\varphi$ says that, in $\mathcal{M} \otimes \mathcal{E}$, all worlds \sim_a -accessible from s satisfy φ . The corresponding worlds in \mathcal{M} are those worlds which are \sim_a -accessible from s and which satisfy $PRE(e)$. Moreover, given that truth values of formulas may change in an update step, the correct description of these worlds in \mathcal{M} is

not that they satisfy φ (which they do in $\mathcal{M} \otimes \mathcal{E}$), but rather $[e]\varphi$: they become φ after the update. Finally, $[e]$ is a partial operation, as $PRE(e)$ has to be true in order to execute e . Putting this together, $[e]K_a\varphi$ says the same as $PRE(e) \rightarrow K_a(PRE(e) \rightarrow [e]\varphi)$. We can simplify this to $PRE(e) \rightarrow K_a[e]\varphi$. Finally, incorporating the uncertainty agents may have concerning events into our consideration, we get axiom 4.

Likewise, the formula $[e]q_a^m$ says that, in $\mathcal{M} \otimes \mathcal{E}$, the agent a assign the value m to the world s where she stands. According to the Addition rule, the value of s in $(\mathcal{M} \otimes \mathcal{E}, s)$ is the sum of the value for s in \mathcal{M} and that for e in \mathcal{E} . Thus the right value for the world s in \mathcal{M} is $m - v_a(e)$. This is what axiom 5 says. \square

Theorem 4 (Completeness) *The logic DEEL is completely axiomatized by the above reduction axioms.*

Proof We have seen the soundness of the above reduction axioms. Note that they are all equivalences, so they are clearly sufficient for eventually turning every formula from the dynamic language into a static one. Then we can use the completeness theorem for our static evaluation language in section 2. \square

One final issue remains to be discussed: do other update rules define a complete logic, and in particular, the Parameterized rule? There is no general results here. But the Parameterized rule does suggest the following reduction axiom. Although it seems a bit clumsy, its validity can be proved in a similar way to axiom 5:

$$[e]q_a^m \leftrightarrow PRE(e) \rightarrow q_a^{m-v_a(e)\cdot\mu(e)\cdot\lambda(e)}$$

However, once we introduce a weight for the previous state, this job becomes harder. If the update rule is functionally expressible, we can still get a complete logic, though clearly substraction will no longer work.

4. Illustration: commands and obligations

So far, we have found a mechanism which represents a plausible view of incoming information that changes preferences. We now illustrate this framework in a different setting, namely deontic logic. Our aim is to show how the logical issues discussed in this paper correspond to real questions of independent interest.

Originally, deontic logic ([2]) was the study of assertions of obligation like ‘it ought to be the case that φ ’ (denoted as $O\varphi$) emanating from some moral authority. The standard truth condition for the expression $O\varphi$ is

$$\mathcal{M}, s \models O\varphi \text{ iff for all } t \in S \text{ such that } s \sim t \text{ and } \mathcal{M}, t \models \varphi.$$

The underlying intuition is that φ ought to be case which are true in *all best possible worlds*, as seen from the current one. This naturally suggests an ordering among worlds, and we will see that this allows for a quantitative interpretation.

Likewise, we can think of the deontic setting dynamically: obligations may be changed due to incoming information, or they can be treated as programs or actions themselves. So far, much research in these dynamic aspects has been carried out by [21], [26], [22], [29] and so on. The recent work [28] takes the dynamic epistemic logic paradigm to obligation changes brought about by acts of commanding in the multi-agent context. Here is the reduction axiom proposed in [28]:

$$[!_a\varphi]O_a\psi \leftrightarrow O_a(\varphi \rightarrow [!_a\varphi]\psi)$$

where the intended interpretation of $O_a\varphi$ is ‘it is obligatory for the agent a ($\in G$) that φ ’, and $[!_a\varphi]$ is intended to represent the action of commanding an agent a to see to it that φ .

It is no surprise that Yamada’s system can be translated into the qualitative relation-changing version of preference update in [10]. This result hinges on the fact that deontic semantics suggest an ordering among possible worlds. Naturally, the mechanism of evaluation update applies to obligation change as well, but with a more refined view. We can now indicate the ‘weight’ of a command in terms of the numerical points, as pictured in the following event model:

$f \circ$	$e \circ$
1	4

where command e has more strength than f does.

In particular, the current approach also is an improvement in the sense that it brings out insights to the issue of *conflicting commands*, which has been discussed in many papers. Let us first look at a variation of the example in [28]:

Example 2 *Suppose you are reading an article in the office you share with your two bosses and a few other colleagues. It is a hot summer noon, the temperature is above 30 degree Celsius. You can open the window, turn on the air conditioner, or concentrate on your reading and ignore the heat. Then your boss A commands you to open the window, your boss B commands you not to do that. What effects do their commands have on the current situation? Which command would you obey?*

A theorem of the form $[!_a(\varphi \wedge \neg\varphi)]O_a\psi$ (Dead End) in [28] handles this problem. It says that contradictory commands lead to an obligational dead end. But this implicitly rules one important aspect, i.e. *the hierarchy of authorities*, out of our scope. Your two bosses may well stand at different authority levels, you may refuse to open the window if your boss B is in a higher position than A . This shows that in a deontic setting, managing conflict is much more than managing consistency. To model the possible contradictory commands carried by different authorities, our cur-

rent system provides at least one new way of doing this by the following rephrased update rule.

Definition 11 (Deontic parameterized rule) *Let $\eta(e)$ be an authority function, and $\lambda(e)$ a relative force function. The domains of these two functions are the set of events, and the ranges are \mathbb{N} . Given the value for the previous state s and event e , the new value for state (s, e) is defined by the following:*

$$v_a(s, e) = v_a(s) + v_a(e) \cdot \eta(e) \cdot \lambda(e).$$

Since we are still in the multi-agent context, the relative force applies here very well. Again the agent a may take the boss's commands seriously, whereas agent b may not.

Note that by introducing hierarchy of authorities into the above update rule, we actually deal with the problem *within* the logic. One promising way to handle this issue is to think of the hierarchy as sort of *outside* meta constraints or priorities ordering. The idea is from Optimality theory (cf. [24]) in which constraints are strictly ordered according to their importance. For a logical investigation concerning priorities and preference change, we refer to [16].

One final remark: we have discussed how evaluation update can deal with deontic reasoning in a dynamic style, adding some new twists, such as evaluation of actions of commanding, and resolving conflicts between commands from different agents. This style of analysis is quite general, and it can also be applied to *default reasoning*. Here agents receive incoming information which does not necessarily eliminate worlds, but changes their evaluations of those worlds: more precisely, the *plausibilities* which they assign to these worlds. A typical example is the instruction 'Normally, φ ' in [27], which changes the preference ordering between worlds so as to give the φ worlds a higher position. For this same purpose, from the perspective of evaluation update, we can take an event model \mathcal{E} including two events "see φ ", "see $\neg\varphi$ " with different values (say +1, 0) to model a default 'Normally φ '. Executing the update with \mathcal{E} leads to a new model where the φ -worlds have all gained one point, upgrading their position in the agent's expectation pattern encoded in the plausibilities. In this way, the dynamic evaluation language becomes a sort of default language, where

The expression ["see φ "] ψ plays the role of a default conditional 'if φ then ψ '.

A complete evaluation default logic (*EDL*) can be deduced directly from our general logic *DEEL*. This new insight leads to the following question, namely, how to compare the overall *DEEL* to default logic in [27]? My conjecture would be that *DEEL* seems to be much richer, because by varying the event values in \mathcal{E} , one can

describe the behavior of a whole *family* of different ‘default conditionals’. It all depends on which strengths the agent wishes to assign to the antecedents of those default conditionals.

5. Further logical issues

To get a good understanding of the expressiveness of the evaluation language presented in section 2 we look at some issues concerning bisimulation, a fundamental notion in modal logics. First we formulate the standard bisimulation definition for evaluation models below. The conditions for the epistemic relations \sim_a are omitted, as they are routine.

Definition 12 (Evaluation bisimulation) *Let $\mathcal{M} = (S, v_a, V)$ and $\mathcal{M}' = (S', v'_a, V')$ be two evaluation models. A non-empty binary relation $Z \subseteq S \times S'$ is called an evaluation bisimulation between \mathcal{M} and \mathcal{M}' if the following conditions are satisfied:*

- (i) If sZs' then s and s' satisfy the same propositional variables.
- (ii) If sZs' and $v_a(s) \leq v_a(t)$ (or $s \preceq_a t$), then there exists t' in \mathcal{M}' such that tZt' and $v'_a(s') \leq v'_a(t')$ (or $s' \preceq_a t'$) (the forth condition).
- (iii) If sZs' and $v'_a(s') \leq v'_a(t')$ (or $s' \preceq_a t'$), then there exists t in \mathcal{M} such that tZt' and $v_a(s) \leq v_a(t)$ (or $s \preceq_a t$) (the back condition).

Example 3 From the view point of the above evaluation bisimulation, it would make sense to identify the following two models, where we identify worlds by their evaluations:



After all, the pure preference pattern is the same in both. But the evaluations make a difference in the evaluation language. Consider the event model \mathcal{E} which updates all φ -worlds (s in the pictures) with 1 each time it is applied. Applying \mathcal{E} once to the model on the left keeps the preference intact, but on the right, it voids it. All this seems to suggest that we need a new bisimulation definition for evaluation models to express the intensity of preferences. Here is one proposal.

Definition 13 (Distance) *The distance between two possible states s and t in an evaluation model is defined as $\mathcal{D}_a(s, t) = |v_a(s) - v_a(t)|$.*

In Example 3 the distance between s and t is 2 in the model on the left, but it is 1 on the right.

Definition 14 (Distance bisimulation) Let $\mathcal{M} = (S, v_a, V)$ and $\mathcal{M}' = (S', v'_a, V')$ be two evaluation models. A non-empty binary relation $Z \subseteq S \times S'$ is called distance bisimulation between \mathcal{M} and \mathcal{M}' if the following conditions are satisfied:

- (i) If sZs' then s and s' satisfy the same propositional variables.
- (ii) If sZs' , $s \leq t (t \leq s)$ and $\mathcal{D}_a(s, t) = k$, then there exists t' in \mathcal{M}' such that tZt' , $s' \leq t' (t' \leq s')$ and $\mathcal{D}_a(s', t') = k$ (the forth condition).
- (iii) If sZs' , $s' \leq t' (t' \leq s')$ and $\mathcal{D}_a(s', t') = k$, then there exists t in \mathcal{M} such that tZt' , $s \leq t (t \leq s)$ and $\mathcal{D}_a(s, t) = k$ (the back condition).

As usual, we say two evaluation models are *bisimilar* when there is some evaluation bisimulation linking two states in the two models. Intuitively, if the *same efforts* (same distance) are made to get from one state to another in each model, then the two models are bisimilar.

This means that with the notion of comparative distance, we can say sentences like ‘ d_1 is preferable over d_2 more than d_1 is preferable over d_3 ’, which simply means $\mathcal{D}(s_1, s_2) > \mathcal{D}(s_1, s_3)$ in the model, where d_1, d_2 and d_3 are chosen in s_1, s_2 and s_3 , respectively. This is what most languages of qualitative preference are not able to do. Following this line may be related somehow to the modal languages for ‘geometry’ studied in [4].

6. Conclusions

We have presented here a quantitative semantic of preference in terms of evaluation functions. A new language with propositional constants was proposed and it turned out to be both concise and expressive. Moreover, such a quantitative perspective suggests a different way to deal with preference changes when processing new information. We followed the standard mechanism of product update, and proposed a new Addition rule and a new Parameterized rule to characterize the subtleties of value changes. A complete dynamic epistemic evaluation logic was presented for the evaluation update. We then shifted to the deontic setting and showed that the current mechanism applies there as well, in particular, it provides a way to solve the issue of contradictory obligations. Finally, we ended up with a new technical result concerning bisimulation for evaluation models. As an immediate follow-up we would like to pursue how these abstract results can be used to analyze further problems in decision theory and game theory.

References

- [1] C. Alchourrón, P. Gärdenfors, and D. Makinson, 1985, “On the logic of theory change: Partial meet contraction and revision functions”, *Journal of Symbolic Logic*, 50:510-530.

-
- [2] L. Åqvist, 1994, “Deontic logic”, in D. Gabbay and F. Guenther(eds.), *Handbook of Philosophical Logic*, Vol. 2, Kluwer, Dordrecht.
- [3] G. Aucher, 2003, *A Combined System for Update Logic and Belief Revision*, MoL-2003-03, ILLC, University of Amsterdam.
- [4] P. Balbiani, V. Goranko, R. Kellerman, and D. Vakarelov, 2007, “Logics for geometric structures”, in M. Aiello, I. Pratt-Hartmann, and J. van Benthem (eds.), *Handbook of Spatial Logics*, Springer.
- [5] A. Baltag, L. S. Moss, and S. Solecki, 1998, “The logic of common knowledge, public announcements, and private suspicions”, in I. Gilboa(ed.), *Proceedings of the 7th Conference on Theoretical Aspects of Rationality and Knowledge (TARK 98)*, pp. 43-56.
- [6] A. Baltag and S. Smets, 2008, “A qualitative theory of dynamic interactive belief revision”, in M. Wooldridge, G. Bonanno, and W. van der Hoek(eds.), *Logic and the Foundations of Game and Decision Theory*, Vol. 3 of *Texts in Logic and Games*, Amsterdam University Press.
- [7] J. van Benthem, 1996, *Exploring Logical Dynamics*, CSLI Publication, Stanford.
- [8] J. van Benthem, 2007, “Dynamic logic for belief revision”, *Journal of Applied Non-Classical Logic*, 17:129-156, Technical Report, PP-2006-11, ILLC, University of Amsterdam.
- [9] J. van Benthem and F. Liu, 2004, “Diversity of logical agents in games”, *Philosophia Scientiae*, 8:163-178.
- [10] J. van Benthem and F. Liu, 2007, “Dynamic logic of preference upgrade”, *Journal of Applied Non-Classical Logic*, 17:157-182, Technical Report, PP-2005-29, ILLC, University of Amsterdam.
- [11] H. van Ditmarsch, W. van der Hoek, and B. Kooi, 2007, *Dynamic Epistemic Logic*, Springer, Berlin.
- [12] J. Gerbrandy, 1999, *Bisimulation on Planet Kripke*, PhD thesis, ILLC, University of Amsterdam.
- [13] P. Girard, 2008, *Modal Logics for Belief and Preference Change*, PhD thesis, Stanford University.
- [14] T. Grune-Yanoff and S. O. Hansson(eds.), 2009, *Preference Change: Approaches from Philosophy, Economics and Psychology*, Theory and Decision Library, Springer.
- [15] S. O. Hansson, 1995, “Changes in preference”, *Theory and Decision*, 38:1-28.
- [16] D. de Jongh and F. Liu, 2009, “Preference, priorities and belief”, in T. Grune-Yanoff and S.O. Hansson(eds.), *Preference Change: Approaches from Philosophy, Economics and Psychology*, pp. 85-108, Theory and Decision Library, Springer.
- [17] J. Lang and L. van der Torre, “From belief change to preference change”, in *Proceedings of ECAI-2008*.
- [18] F. Liu, 2004, *Dynamic Variations: Update and Revision for Diverse Agents*, MoL-2004-05, ILLC, University of Amsterdam.
- [19] F. Liu, 2008, *Changing for the Better: Preference Dynamics and Agent Diversity*, PhD thesis, ILLC, University of Amsterdam.
- [20] F. Liu, 2009, “Diversity of agents and their interaction”, *Journal of Logic, Language and Information*, 18(1):23-53.
- [21] J-J. Ch. Meyer, 1988, “A different approach to deontic logic: Deontic logic viewed as a variant of dynamic logic”, *Notre Dame Journal of Formal Logic*, 29:109-136.
- [22] R. van der Meyden, 1996, “The dynamic logic of permission”, *Journal of Logic and Computation*, 6:465-479.
- [23] J. A. Plaza, 1989, “Logics of public announcements”, in *Proceedings of the 4th International Symposium on Methodologies for Intelligent Systems*.
- [24] A. Prince and P. Smolensky, 1993, *Optimality Theory: Constraint Interaction in Generative Grammar*, Blackwell, Malden, Massachusetts.
- [25] W. Spohn, 1988, “Ordinal conditional functions: A dynamic theory of epistemic states”, in W.L. Harper and B. Skyrms (eds.), *Causation in Decision, Belief Change and Statistics II*, pp. 105-134.

- [26] L. van der Torre and Y. Tan, 1999, “An update semantics for deontic reasoning”, in P. McNamara and H. Prakken(eds.), *Norms, Logics and Information Systems*, pp. 73-90, IOS Press.
- [27] F. Veltman, 1996, “Defaults in update semantics”, *Journal of Philosophical Logic*, 25:221-261.
- [28] T. Yamada, 2006, “Acts of commands and changing obligations”, in K. Inoue, K. Satoh, and F. Toni(eds.), *Proceedings of the 7th Workshop on Computational Logic in Multi-Agent Systems (CLIMA VII)*, Revised version appeared in *LNAI 4371*, pp. 1-19, Springer-Verlag, 2007.
- [29] B. Zarnic, 2003, “Imperative change and obligation to do”, in K. Segerberg and R. Sliwinski(eds.), *Logic, Law, Morality: Thirteen Essays in Practical Philosophy in Honour of Lennart Aqvist*, pp. 79-95, Uppsala philosophical studies 51, Department of Philosophy, Uppsala University, Uppsala.

偏好变化的一个量化模型

刘奋荣

清华大学人文社会科学学院哲学系

fenrong@tsinghua.edu.cn

摘 要

偏好是哲学、博弈论、决策论和效益理论等学科的核心概念，偏好及其逻辑性质在行为哲学和理性选择理论中尤其占有十分重要的地位。偏好的概念使得我们对世界的看法变得多姿多彩，它驱使着我们在尘世的种种行为选择。然而，偏好不是静止不变的，建议、命令、以及其他的信息不断改变着我们的偏好。近年来，逻辑学家们开始对偏好的改变进行深入的研究。到目前为止，关于偏好变化的模型主要有以下两种：第一、采取AGM理论研究偏好变化，给出变化的逻辑公设。第二、采用新近发展起来的动态认知逻辑的方法，对偏好的具体变化机制进行研究，给出动态偏好逻辑系统。无论是上面提到的哪种方法，都是采用定性的视角，即，偏好被表示成一个序关系。与此相反，本文采取量化的视角来研究偏好，利用偏好赋值函数给出偏好的量化语义。就逻辑语言而言，我们给出一个包括命题常元的新语言。这个语言既简练又富于表达力。基于这样的量化语义，处理偏好变化的方法就与以往的方法有所不同。根据经典的乘积更新的机制，我们提出了新的加法规则和一个参数化规则，来刻画偏好赋值的细微变化之处。同时，我们给出一个动态认知赋值逻辑，并证明其完全性。此外，我们还考虑道义逻辑最近的一些研究成果，表明本文给出的模型同样适用于道义的情境。特别是，这个新的模型能够解决困扰人们已久的义务冲突问题。最后，针对赋值偏好模型，我们定义了适用于它“赋值互模拟”。而且，我们还进一步给出了一个新的互模拟概念“距离互模拟”以结束本文。